



TRAFFIC SAFETY SUPPLY COMPANY

Your Traffic Sign & Supplies Resource Since 1956

MOUNTING HARDWARE



THDW-100 ELECTROLIER MOUNTING SET

Fits any size post from 3" diameter to 8-1/2" diameter. Includes:
30" strap, flared leg bracket, hex bolt and washer, strap buckle with fastener bolt.
2/SET #16500700



3/8" GALVANIZED BOLTS

- 3" #16801955
- 3-1/2" #16801956
- 4" #16801957
- 4-1/2" #16801958
- 5-1/2" #16801960
- 6" #16801961
- 6-1/2" #16801969
- 7-1/2" #16801965
- 8" #16801966
- 8-1/2" #16801967
- 9" #16801968




THDW-600 3/8" x 3" Galvanized Steel Lag Bolt #16801900



3/8" NUT Galvanized #16802104



5/16" X 1/2" BOLT WITH NEOPRENE WASHER #16502815



3/8" WASHERS

- A. Nylon #16802103
- B. Galvanized #16802100
- C. Stainless Steel #16801835



POST CLIP ASSEMBLY

Used to mount Interstate signs with extruded keyways to I Beam post flanges.

Aluminum post clip and bolt, nylon nut and washer.

- #16501800 Aluminum post clip, stainless steel bolt, nut, and washer.
- #16501801

THEFT RESISTANT HARDWARE



CHEVRON BRACKET

Mount 2 signs to a single post. Adjustable aluminum bracket mounts two chevron signs to a single post. The angle of the signs can be adjusted after installation.

Fits sign sizes:
12"x18" and 18"x24"
#16504750
18"x24" and 24"x30"
#16504760
24"x30" and 30"x36"
#16504770

TUFNUT

- Theft Resistant
- Requires no special tools
- Completely reusable
- Reduces Liability

Installation:

- A. Install Tufnut #1 Finger tight.
- B. Install Tufnut #2 so it's half a turn from #1 and tighten or loosen by inserting wrench or vicegrip between tufnuts, then turning both nuts.
- C. Remove Tufnut #2 leaving Tufnut #1 properly secured.



- 5/16" Security Nut #16502700
- 5/16" x 2-1/2" Carriage Bolt #16502800
- 5/16" x 3" Carriage Bolt #16502801
- 3/8" Security Nut #16502701

DRIVE RIVETS

- 3/8" Standard Aluminum #16502205
- 3/8" Standard Steel #16502200
- 3/8" Steel Pin Aluminum Shell #16502225
- 3/8" Steel Pin Steel Shell #16502215



VANDLGARD

The Vandlgard nut is an effective, easy to use, vandal/theft resistant nut. Simply thread it onto a standard bolt or round-head bolt and tighten just as you would a standard nut. When the Vandlgard nut is tight it will break off leaving a cone on the bolt. Vandals will not be able to grip remaining cone with wrench or pliers.

Available in Zinc or Aluminum

- 5/16" Zinc #16803200
- 5/16" Aluminum #16803192
- 3/8" Zinc #16803192
- 3/8" Aluminum #16803194



THEFT RESISTANT BOLT WITH NYLON WASHER

- 5/16" x 1/2"
- 100 bolts per box, 1 tool per box
- #16502802
- Additional Tool
- #16502810